



POWERFLEX™ AE GAS

Powerful Air and Generator Power With Dual Functionality.

The versatile PowerFlex™ AE Gas offers reliable, continuous rotary screw performance and integrated brushless AC power for exceptional jobsite performance. The PowerFlex™ AE Gas is ideal for general construction, monument engraving, service vehicles, and roadside repairs.

- **Engine:** Vanair® VNR750EFI, 25 HP
- **Air Compressor:** Rotary screw, 40 CFM, 175 PSI max ¹
- **Generator:** 7kW peak, 6.8kW continuous, AC power, 60Hz, single phase ²
- **Drive System:** Belt-driven
- **Fuel Capacity:** 12 gallon integral tank or tied to chassis ³
- **Air Storage Capacity:** 4 gallon integrated ⁴

¹ Air Compressor is factory set to 150 PSI

² Available in 5.7kW continuous @ 50Hz

³ Available without integral fuel tank

⁴ Standard version only; sold separately for compact version



Also available in a compact version



800.526.8817 | vanair.com   

POWERFLEXAEGAS_082426NML

POWERFLEX™ AE GAS MODULAR SYSTEM

KEY FEATURES

- Fuel system can be integrated with the chassis
- True two-generator system for safe multi-function of welder & electric tools
- Galvannealed powder-coated sheet metal for protection
- 100% duty, high-frequency welder offering excellent weld characteristics
- Heavy-duty belt-driven system for anti-vibration & long service intervals
- Remote mount control panel for ultimate convenience
- Integrated lift hook & battery tray
- Designed for easy maintenance
- Small footprint, designed to fit on side pack or behind cab

Engine

- Vanair® VNR750EFI, 25 HP
- Electric start
- Electronic governor for quick throttle response & stability
- Electronic fuel injected

Air Compressor

- Rotary screw compressor, encapsulated
- 40 CFM, 175 PSI max (factory set @ 150 PSI)

Generator

- 6.8kW continuous @ 60Hz ¹
- Brushless AC design
- Smooth wave for minimal distortion
- 120V & 240V outlets provided

Fuel Capacity

- 12 gallon integral tank or tied to chassis ²

Air Storage Capacity

- 4 gallon integrated ³

Remote Control Panel (Optional)

- Provides ultimate user convenience & safety
- All functions accessible at panel
- Harness options available

Options/Accessories

- Remote control panel
- Remote panel harness extensions
- Air hoses, hose reels & fittings
- OSHA safety valve (velocity fuse)
- Filter/lubricator/regulator (FLR)
- Air reservoirs
- Service/control line moisture separators
- Tool oiler/lubricator
- Air aftercooler
- Remote condensation drain
- AC generator outlet box
- Vibration isolator kits
- GFCI kits
- Maintenance kits - engine & compressor
- Cold weather kits
- Machine covers

Dimensions/Weight

- 47.1L x 21.1W x 30.9H - standard version
- 47.5L x 24.2W x 34.1H with fittings - standard version
- 47.2L x 21W x 24.5H - compact version
- 48.2L x 24.6W x 24.5H with fittings - compact version
- 575-675 lbs. dry weight (depending on platform)

¹ Available in 5.7kW continuous @ 50Hz

² Available without integral fuel tank

³ Standard version only; sold separately for compact version

Vanair® reserves the right to make changes in engineering, design, and specifications, add improvements, or discontinue manufacturing at any time, without notice or obligation. Vanair®, the Vanair® logo and MOBILE POWER SOLUTIONS® are registered trademarks or trademarks of Vanair®, a Lincoln Electric Company, Michigan City, IN, USA. © 2026 All Rights Reserved.



VANAIR®
A Lincoln Electric Company

800.526.8817 | vanair.com