

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Type:</b>                | Vanair® Start-All® Jump-Pack 2500A 12V. In current production.                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>12V Start:</b>           | Capable of delivering 33,300 joules for 5 seconds discharge during crank attempts. Can jump-start gasoline and diesel engines up to 6L.                                                                                                                                                                                                                                                                                                                |
| <b>Safeties:</b>            | Protect-All® safety technology which includes reverse polarity, short circuit, low current, over current, over charge, over discharge, and over temperature protections. Display that shows charge level and status of the Start-All® Jump-Pack. Illuminated ON/OFF switch to show when the Start-All® Jump-Pack is turned on. Error codes and audible indicator when errors are present. Time out function to prevent excessive drain of the battery. |
| <b>Starting Cables:</b>     | 7 gauge, 24" for each clamp, 54" combined length                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Machine Weight:</b>      | 4.5 (Lbs.)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Dimensions:</b>          | 8.75L x 3.48W x 9.27H (inches)                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Battery:</b>             | Lithium-ion cobalt, 74 watt-hours. Battery has a peak output of 2500A.                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Voltage:</b>             | 14.8VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Storage Temperature:</b> | 40°F to 75°F (4°C to 24°C)                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Accessories:</b>         | 18VDC 100-240VAC wall charger, 18VDC port charger, 3-in-1 cord with USB lightning®, USB-C, and micro-USB connectors, safety strap, carabiner and clip.                                                                                                                                                                                                                                                                                                 |
| <b>Instrument Panel:</b>    | Main ON/OFF switch, LED status display, error indicator LED, accessory output ON/OFF button, (4) USB ports – 5V 2.1A, (2) 6mm ports – 12V 3.5A, (1) aux port – 12VDC 10A, (1) Inverter Receptacle – NEMA 5-15R 120VAC 200W, (1) 3.5mm input charging port – 18VDC 1A, and LED work light with 3 display modes on the rear of the pack including SOS and strobe emergency lights.                                                                       |
| <b>Enclosure:</b>           | Rugged plastic housing with carrying handle and corner bumpers. There is space to stow the cables inside the housing.                                                                                                                                                                                                                                                                                                                                  |
| <b>Service Centers:</b>     | No user serviceable parts inside contact Vanair®.                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Warranty:</b>            | One year from retail purchase date.                                                                                                                                                                                                                                                                                                                                                                                                                    |